

**Application Segments** 

## COLD WORK TOOL STEELS

Cold Work			
Available Product Variant	S		
Long Products* * Presented data refer exclusivly	Plates to long products. Please observe the de	tailed explanations at th	e end of the data sheet (pdf).
Product Description			
BÖHLER K313 is corresponds to deburring dies and punches, cutt Process Melting	the material 1.2362 (X63CrMoV5 1). Bo ing plates and punches, hot shears, ejec	ÖHLER K313 is used fo ction pins, drop-forging (	r intermediate rolls in multi-roll stands, dies and hole punches.
Airmelted			
Properties			
<ul> <li>&gt; Toughness &amp; Ductility : good</li> <li>&gt; Wear Resistance : good</li> <li>&gt; Compressive strength : high</li> <li>&gt; Dimensional stability : good</li> </ul>			
Applications			
<ul> <li>Machine knife (for producers)</li> <li>Fine Blanking, Stamping, Blar</li> </ul>		<ul><li>&gt; Rolling</li><li>&gt; Rolls</li></ul>	> Cold Forming
Technical data			
Material designation			
1.2362 X63CrMoV5-1	SEL EN		
	<u></u>		
Chemical composition (w	t. %)		

С	Si	Mn	Cr	Мо	Ni
0.63	1.10	0.40	5.30	1.20	0.30





## Material characteristics

	Compressive strength	Dimensional stability during heat treatment	Toughness	Wear resistance abrasiv
BÖHLER K313	****	***	***	***
BÖHLER K305	****	***	**	****
BÖHLER K306	****	***	****	***
BÖHLER K320	***	***	***	***
BÖHLER K329	***	***	****	****
BÖHLER K600	*	***	****	*
BÖHLER K601	*	***	****	**
BÖHLER K605	**	***	****	*

## **Delivery condition**

Annealed			
Hardness (HB)		max. 240	
Heat treatment	:		
Annealing			
Temperature	800 to 850 °C	Slow controlled cooling in furnace at a rate of 10 to 20 °C/hr (18 to 36 °F/hr) down to approximately 600 °C (1112 °F)    Further cooling in air.	
Stress relieving			
Temperature	650 °C	After through heating, hold in neutral atmosphere for 1-2 hours.    Slow cooling in furnace Intended to relieve stresses caused by extensive machining or in complex shapes.	
Hardening and Ter	mpering		
Temperature	980 to 1,020 °C	Quenching: Oil, salt bath (450 to 500 °C   842 to 932 °F), air (small sizes only)    Holding time after temperature equalization: 15 to 30 minutes.	

If other available product variants are listed in addition to long products, please note that these may differ in terms of melting process, technical data, delivery and surface condition as well as available product dimensions. For mandatory technical specifications, other requirements and dimensions, please contact our regional voestalpine BÖHLER sales companies. The data contained in this brochure is merely for general information and therefore shall not be binding on the company. We may be bound only through a contract explicitly stipulating such data as binding. Measurement data are laboratory values and can deviate from practical analyses. The manufacture of our products does not involve the use of substances detrimental to health or to the ozone layer.

## voestalpine BÖHLER Edelstahl GmbH & Co KG

Mariazeller Straße 25 8605 Kapfenberg, AT T. +43/50304/20-0 E. info@bohler-edelstahl.at https://www.voestalpine.com/bohler-edelstahl/de/

