

TITANIUM AND TITANIUM ALLOYS

Available Product Variants

Plates

Product Description

Bohler L512 is a non-alloyed grade with high corrosion resistance in various environments and excellent ductility with good mechanical properties.

Applications

- > Medical
 - > CPI (incl. LNG, Urea)
- > Medical Instruments & Implants
 - > Components for Chemical plants (incl. LNG, FGD, Urea, LDPE, etc.)
- > Other Oil and Gas + CPI components

Technical data

Material designation		Standards	
Grade 2	Market grade	ISO 5832-2	EN ISO
Grade 2H		17850	DIN
3.7035	SEL	17860	
R50400	UNS	B265	
		F67	
		VdTÜV-WB230/1	Others

Chemical composition (wt. %)

C	Fe	N	O	H	Others
max. 0.08	max. 0.30	max. 0.03	max. 0.25	max. 0.015	max. 0.1

Related to ASTM B265

If other available product variants are listed in addition to long products, please note that these may differ in terms of melting process, technical data, delivery and surface condition as well as available product dimensions. For mandatory technical specifications, other requirements and dimensions, please contact our regional voestalpine BÖHLER sales companies. The data contained in this brochure is merely for general information and therefore shall not be binding on the company. We may be bound only through a contract explicitly stipulating such data as binding. Measurement data are laboratory values and can deviate from practical analyses. The manufacture of our products does not involve the use of substances detrimental to health or to the ozone layer.

voestalpine BÖHLER Edelstahl GmbH & Co KG

Mariazeller Straße 25
 8605 Kapfenberg, AT
 T. +43/50304/20-0
 E. info@bohler-edelstahl.at
<https://www.voestalpine.com/bohler-edelstahl/de/>